

# BLANKE BASEMAX

BLANKE BASEMAX is a lightweight levelling compound used to create even composite substrates before laying BLANKE PERMATFLOOR and BLANKE PERMATOP. The 2-component system consists of a lightweight levelling compound made of expanded glass granulate and a cementitious binder. This lightweight levelling compound makes it possible to level uneven surfaces from 5 to 100 mm in indoor areas. Approx. 4.8 kg of material per m<sup>2</sup> are required for a thickness of 1 cm. It is particularly lightweight, quick drying and ready for laying coverings on after just 12 hours. Blanke floor systems with a the tile layer can subsequently be installed quickly.



## BLANKE BASEMAX

### COMPONENT A (BINDER)

1 25 kg bag, mixing ratio  
A+B by weight 1:1 PU: 1 bag

Art. no.	€/kg
288-900	6.18

## BLANKE BASEMAX

### COMPONENT B (LIGHTWEIGHT FILLER)

1 12.5 kg bag, mixing ratio  
A+B by weight 1:1 PU: 1 bag

Art. no.	€/kg
287-900	6.18

### Advantages:

- > Mixing ratio by weight 1:1
- > Lightweight, low static load
- > Good coverage due to high proportion of lightweight ingredients
- > 2-component mix creates permanent, secure bonding
- > Quick drying
- > Ready for laying after 12 hours